

ALARM CABLE ALHF LSZH Cca s1a,d0,a1

TECHNICAL FEATURES

CONDUCTORS

Flexible red copper

INSULATION

LSZH M1 (Low smoke emission)

ASSEMBLY

conductors stranded in layers

SCREEN

Aluminium/Polyester tape

Drain wire flexible red copper

JACKET

LSZH M1 (Low smoke emission) White

PACKAGING AVAILABLE



100/200 mt.



500 mt.

MARKING

KTS [cod] ALHF-C LSZH IEC 60332-1 CEI UNEL 36762 C4 (Uo=400V)

EUROCLASSE Cca s1,d0,a1 2019 (meter) BATCH week/Year MADE IN ITALY

COLOUR CONDUCTOR

Table n° 001

ELECTRICAL FEATURES

TEST VOLTAGE

1000 V

INSULATION RESISTANCE

> 200 MΩ/Km

TEMPERATURE RANGE

-10° / +70°

BENDING RADIUS

10 X Ø

STANDARDS

Insulation and sheath

CEI EN 50363

Flame retardant

IEC 60332-1-2

Fire retardant

IEC 60332-3-25

Low smoke emission

CEI EN 50267-2-3

coexistence with cables CAT. 1

UNEL 36762

European directive Rohs 2011/65/EU

CPR REACTION CLASS

Harmonized standard

EN 50575:2014 + A1:2016

Reaction to fire

Cca s1a,d0,a1

Hazardous substance

Nothing

