



Delock 3G-SDI Splitter 1 in > 4 out

Description

This SDI splitter by Delock can be used to receive signals of one SDI input source, such as a DVR, an HD-SDI camera or other SDI device, to up to 4 different output devices such as SDI monitors.



Specification

- Connectors:
 - Input:
 - 1 x BNC female (3G-SDI)
 - 1 x 5 V DC jack
 - Output:
 - 4 x BNC female (3G-SDI)
- Supported resolution:
 - SD 480i, 525i and 625i
 - HD 720p 24, 25, 30, 50 and 60 Hz
 - HD 1080i 50, 60 Hz
 - HD 1080p 24, 25, 30, 50 and 60 Hz
- Robust metal housing
- Power consumption: max. 1.2 W
- Dimensions (LxWxH): ca. 162 x 82 x 25 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: $\varnothing$ ca. 2.1 mm
 - outside: $\varnothing$ ca. 5.5 mm
 - length: ca. 9 mm

Package content

- 3G-SDI splitter
- Power supply

Item no. 93250

EAN: 4043619932504

Country of origin: China

Package: White Box

Images

