


Mod. ER17338-187.BEW**ROTO-MOLDED LONG CASE ER17338-187**

Rotomolded case made in high density polyethylene.

PU o-ring, hinged lid with steel wire lid supports, 6 foldable recessed handles to grant easy transportability even when the case is fully loaded, two silent wheels with ball bearings, recessed metal butterfly latches with padlock ring, two automatic purge valves.



METRIC MM-KG-C°

**INTERNAL DIMENSIONS**

L LENGTH	1735 mm
W WIDTH	380 mm
D DEPTH	250 mm
LID	70 mm
BASE	180 mm


EXTERNAL DIMENSIONS

L LENGTH	1820 mm
W WIDTH	470 mm
D DEPTH	295 mm

OTHER DATA

WEIGHT EMPTY	27 Kg
WEIGHT WITH FOAM	Kg
WEIGHT WITH CUSTOM FOAM	Kg
VOLUME	167 lt
BUOYANCY	108 Kg/max
OPERATING TEMPERATURE	°C min / max

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS

L LENGTH	68.30 in
W WIDTH	14.96 in
D DEPTH	9.84 in
LID	2.75 in
BASE	7.08 in

EXTERNAL DIMENSIONS

L LENGTH	71.65 in
W WIDTH	18.50 in
D DEPTH	11.61 in

OTHER DATA

WEIGHT EMPTY	59.52 lbs
WEIGHT WITH FOAM	lbs
WEIGHT WITH CUSTOM	lbs
FOAM	
VOLUME	44.11 gal
BUOYANCY	238.10 lbs/max
OPERATING	°F min / max
TEMPERATURE	

FEATURES



AUTOMATIC VALVE

Automatic pressure release valve.



SEALING O-RING

(Art. NEOSEAL + nr. art.)



WHEELS WITH BEARINGS



HEAVY DUTY METAL LATCHES

8 heavy duty metal latches, 4 on each longer side, grant a more reliable retaining during rough handling.

ACCESSORIES

SPARE PARTS