

Locking Devices, Twist-Lock®,
Valise, Male Plug, 30A 250V, 2-Pole
3-Wire Grounding, L6-30P, Screw
Terminal, Black

By Hubbell Wiring Device-Kellems
Catalog # [HBL2621VBK](#)

Twist-Lock® Vasile®, Plug, 30A 250V, 2-Pole 3-Wire Grounding,
NEMA L6 Nylon.

Features

- Powerful cord grip prevents conductor slippage and strain on wiring terminals
- Totally insulated impact and crush resistant nylon body
- Unique patented clamp type terminals provide a superior electrical connection by bundling the conductor strands when clamps are tightened

Performance

- Electrical - Current Interrupting - Certified for full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - HB or better per UL 94 or CSA 22.2 No. 0.6
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperature - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Terminal Accommodation - #14 AWG - #8 AWG stranded copper wire only.
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

General

Catalog Number	HBL2621VBK
Cord Range	0.590"-0.930" (15.0-23.6)
EU RoHS Indicator	Contact Manufacturer
Horsepower - Maximum	2
Item Type	30A Valise® Plug
Material	Nylon
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Specifications	• Blades - Brass • Clamp Screws - #8 - 32 Steel - Zinc plated (Philips / Slotted / Robertson) • Housing - Black nylon • Terminal Clamps - Steel - Nickel plated



UPC	• Terminal Screws - #8 - 32 Steel (Philips / Slotted / Robertson) 783585043166
-----	---

Dimensions

Dimensions	2.5 in x 1.78 in x 1.78 in
Display Size	Standard Sized
Height	1.78 in
Length	2.5 in
Weight	0.3 lb
Width	1.78 in

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	30 A
Current Rating	30 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	250 VAC
Voltage Rating Description	250 VAC

Conductor Related

Cord Type	All Listed Portables
Number Of Wires	3-Wire Grounding
Wire Size	#14 AWG to #8 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498
Nema Rating	L6-30P
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
-----------------	----

Pallet Quantity2640

Product Assets

Catalog Page - WDK B-28 Catalog Page
Catalogs - WDK Catalog Full 2024

Installation Manuals - WIRING_PD2585_INSTALLINST
Sales Drawings - WDK_HBL2621V_DRAWING_PDF
Specifications - HBL2621VBK Specification Sheet French
Specifications - Wiring HBL2621VBK Specification Sheet
Warranty - Industrial & Commercial Products



A Hubbell brand