

Straight Blade Devices,  
Receptacles, 4- Plex,  
Commercial/Industrial Grade, 2-  
Pole 3-Wire Grounding, 15A 125V, 5-  
15R, Ivory, Single Pack

By Hubbell Wiring Device-Kellems  
Catalog # [HBL415I](#)

Straight Blade Devices, Receptacles, 4- Plex,  
Commercial/Industrial Grade, 2-Pole 3-Wire Grounding, 15A  
125V, 5- 15R, Ivory, Single Pack.

Application

- Industrial

Performance

- Electrical - Current Interrupting - Capable of withstanding a fault level of 1000A, per UL498
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-12 AWG stranded or solid copper conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

|                              |                                                                                                                                                                                         |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Catalog Number               | HBL415I                                                                                                                                                                                 |
| Color                        | Ivory                                                                                                                                                                                   |
| EU RoHS Indicator            | Yes                                                                                                                                                                                     |
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means                                                                                                                                         |
| Horsepower - Maximum         | 0.5                                                                                                                                                                                     |
| Item Type                    | 4-PLEX                                                                                                                                                                                  |
| Material                     | Polycarbonate                                                                                                                                                                           |
| Material - Mounting Hardware | Screw Mounting                                                                                                                                                                          |
| Number Of Poles              | 2-Pole                                                                                                                                                                                  |
| Operating Temperature        | Maximum continuous 75°C and minimum -40°C without Impact                                                                                                                                |
| Series                       | 4-Outlet Receptacle                                                                                                                                                                     |
| Specifications               | <ul style="list-style-type: none"><li>Base - PBT</li><li>Face - Polycarbonate</li><li>Ground Contacts - .031 in. (.8) Brass</li><li>Ground Plate - .032 in. (.8) Plated Steel</li></ul> |



UPC

- Power Contacts - .032 in. (.8) Brass
- 783585013770

Dimensions

|              |                             |
|--------------|-----------------------------|
| Dimensions   | 4.30 in x 0.92 in x 4.30 in |
| Display Size | Standard Sized Product      |
| Height       | 4.3 in                      |
| Length       | 4.3 in                      |
| Weight       | 0.4 lb                      |
| Width        | 0.92 in                     |

Electrical Ratings

|                            |                           |
|----------------------------|---------------------------|
| Amperage Rating            | 15 A                      |
| Connectivity               | Screw Terminals           |
| Current / Amperage Rating  | 15 A                      |
| Current Rating             | 15 A                      |
| Dielectric Strength        | Withstands 2,000V minimum |
| Phase                      | Single Phase              |
| Voltage Rating             | 125 V                     |
| Voltage Rating Description | 125 V                     |
| Wattage                    | 1875 W                    |

Conductor Related

|                 |                    |
|-----------------|--------------------|
| Number Of Wires | 3-Wire             |
| Wire Size       | #14 AWG to #12 AWG |

Certifications And Compliance

|                                    |                                                                                                                                                                  |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Industry Standard(s)               | <ul style="list-style-type: none"><li>Certified to CSA 22.2, No. 42 File 285</li><li>Listed to UL Standard 498 File E2186</li><li>NEMA® WD-6 Compliant</li></ul> |
| Nema Rating                        | 5-15R                                                                                                                                                            |
| Standards - RoHS Compliance Status | CM                                                                                                                                                               |

Logistics

Carton Quantity 5

Catalogs - WDK Catalog Full 2024  
Specifications - HBL415I  
Warranty - Industrial & Commercial Products

Product Assets

