

Straight Blade Devices, Male Plug,
Insulgrip-Heavy Duty,
Industrial/Commercial Grade,
Straight, 2-Pole 3- Wire Grounding,
15A125V, 5-15P and White

By Hubbell Wiring Device-Kellems
Catalog # [HBL5266C](#)

Straight Blade Devices, Male Plug, Insulgrip-Heavy Duty,
Industrial/Commercial Grade, Straight, 2-Pole 3- Wire Grounding,
15A125V, 5-15P, Black and White, Single Pack.

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 HB or better
- Environmental - IP Suitability - IP20
- Environmental - Operating Temperatures - Maximum continuous 75°C minimum -40°C (w/o impact)
- Mechanical - Terminal Accommodation - #18-10 AWG. Standed copper wire only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5266C
EU RoHS Indicator	Contact Manufacturer
Material	Polycarbonate
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Insulgrip®
Specifications	• Assembly Screws - Nickel plated steel • Blade Holder - Nylon • Blades - .060 in. (1.5) Brass • Housing/Cord Clamp - Nylon • Terminal Clamp - Nickel plated steel • Terminal Retainer - Clear Polycarbonate • Terminal Screws - #8-32 Brass , multiple drive
Style	Standard
UPC	783585173009

Dimensions

Dimensions	1.52 in x 1.52 in x 1.96 in
------------	-----------------------------



Height	1.96 in
Length	1.52 in
Weight	0.15 lb
Width	1.52 in

Electrical Ratings

Amperage Rating	15 A
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 VAC
Voltage Rating Description	125 V

Conductor Related

Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• CSA Certified to C22.2 No. 42 File 280 • Fed. Spec. W-C596G • NEMA® WD-6 Compliant • UL Listed to UL498 File E1706
Nema Rating	5-15P
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
Pallet Quantity	3600

Product Assets

[Catalog Page - WDK A-66](#) [Catalog Page](#)
[Catalog Page - WDK A-38](#) [Catalog Page](#)
[Catalog Page - WDK K-19](#) [Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)

Engineering Drawing - HBL5266C AutoCAD Drawing
Installation Manuals - WIRING_PD2437_INSTALLINST
Literature - Insulgrip® Straight Blade and Twist-Lock® Devices
Literature - Wiring Device Solutions for Strategic Manufacturing
Facilities
Literature - Entertainment Product Solution Guide
Literature - Industrial Solutions
Literature - Emergency Preparedness for Healthcare

Product Cross Section Image(s) -
WBP_HBL5266C_LINEDIAGRAM_PRODIMAGE
Sales Drawings - WDK_HBL5266_DRAWING_PDF
Specifications - Wiring HBL5266C Specification Sheet
Specifications - HBL5266C Specification Sheet French
Warranty - Industrial & Commercial Products
Video - Insulgrip Twist-Lock and Straight Blade Devices



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK_CA-HBL5266C-SPEC-EN | REV 10/2024