

Straight Blade Devices

Technical Information

Insulgrip® Plugs and Connector Bodies



HBL5266C



HBL5269C

Specifications

Plugs	Part	Description
Typical Specification – Catalog No. HBL5266C	Plug	15A
Manufacturer's Identification – Hubbell HBL5266C	Housing	Nylon – Black
Description – Straight Body Plug	Blade Holder	Nylon – Natural
Type – 2 Pole, 3 Wire, Grounding	Retainer	Polycarbonate – Clear
Rating – 15A, 125V	Cord Clamp	Nylon – Natural
Verified to Fed. Spec. WC596	Contact Blades	.060 in. (1.5) Brass
Certification – UL Listed to UL498 File E1706,	Ground Contact Blade	.040 in. (1.0) Copper Alloy
CSA Certified to C22.2 No. 42 File 280	Line Terminal Screws	#8-32 Brass, Multiple Drive
IP Suitability – IP20	Ground Screw	#8-32 Brass, Multiple Drive (Green)
	Wire Clamps	.062 in. (1.6) Steel – Nickel Finish
Connector Bodies	Part	Description
Typical Specification – Catalog No. HBL5269C	Connector Body	15A
Manufacturer's Identification – Hubbell HBL5269C	Housing	Nylon – Black
Description – Straight Body Connector	Contact Holder	Nylon – Natural
Type – 2 Pole, 3 Wire, Grounding	Retainer	Polycarbonate – Clear
Rating – 15A, 125V	Cord Clamp	Nylon – Natural
Verified to Fed. Spec. WC596	Power Contacts	.040 in. (1.0) Copper Alloy
Certification – UL Listed to UL498 File E1706,	Line Terminal Screws	#8-32 Brass, Multiple Drive
CSA Certified to C22.2 No. 42 File 280	Ground Screw	#8-32 Brass, Multiple Drive (Green)
IP Suitability – IP20	Wire Clamps	.062 in. (1.6) Steel – Nickel Finish

Performance

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V or 250V as rated.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL498 and CSA (Brass, White, Green).
Terminal Accommodation	#18-10 AWG copper conductors only.
Product Identification	Ratings are a permanent part of the device.
Torque Range	12 in./lb. terminal screws, 7 in./lb. assembly screws.
Cord Diameter Range	.230–.720 in. (5.8–18.3) integral cord grip.
Environmental – Material	
Flammability	UL 94HB or better.
Operating Temperature	Maximum continuous 75°C; minimum – 40°C (w/o impact).