

Straight Blade Devices,
Receptacles, Duplex, Industrial
Grade, 2-Pole 3-Wire Grounding,
20A 125V, 5-20R, Black, Single Pack

By Hubbell Wiring Device-Kellems
Catalog # [HBL5362BK](#)



Straight Blade Devices, Receptacles, Duplex, Industrial Grade, 2-Pole 3-Wire Grounding, 20A 125V, 5-20R, Black, Single Pack

Application

- Extra Heavy Duty Specification Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - Top: UL 94V-2, Base: UL 94V-0
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5362BK
Color	Black
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Item Type	Traditional Duplex
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	Extra Heavy Duty
Specifications	• Automatic Self-grounding Clip - Stainless steel • Base - PBT • By-Pass Power Contacts - .036". (.9) Brass • Clamping Plate - Nickel plated brass • Face - Nylon

	• Ground Contacts - .031 in. (.8) Brass • Mounting Screws - Zinc plated steel • Mounting Strap - .050 in. (1.3) Brass • Terminal Screws - Plated brass
Style	Finder Groove Face
Type	Standard Duplex
UPC	783585435244

Dimensions

Dimensions	3.28 in x 1.65 in x 1.19 in
Display Size	Standard Sized Product
Height	1.19 in
Length	3.28 in
Weight	0.25 lb
Width	1.65 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired Screw Terminals
Current / Amperage Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125 V
Wattage	2500 W

Conductor Related

Number Of Wires	3-Wire
Wire Size	#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA 22.2, No. 42 File 285 • Fed. Spec. W-C-596 • NEMA® WD-6 Compliant
----------------------	--

Nema Rating

Standards - RoHS Compliance

Status

5-20R

CM

• UL Listed to UL498 File No.

E2186

Carton Quantity

Pallet Quantity

10

4500

Product Assets

- Catalogs - [WDK Catalog Full 2024](#)
- Specifications - [HBL5362BK](#)
- Warranty - [Industrial & Commercial Products](#)

Logistics

