

HUBBELL
Wiring Device-Kellems

**Locking Devices, Twist-Lock®,
Isolated Ground Industrial, Flush
Receptacle, 20A 125V, 2-Pole 3-
Wire Grounding, L5-20R, Screw
Terminal, Orange**

By Hubbell Wiring Device-Kellems
Catalog # [IG2310](#)

Locking Devices, Twist-Lock®, Isolated Ground Industrial, Single
Flush Receptacle, 20A 125V, 2-Pole 3-Wire Grounding, NEMA L5-
20R, Screw Terminal, Orange Nylon face.



Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)
- Mechanical - Flammability - V2 or better per UL94/CSA 22.2 No.0.17
- Mechanical - Terminal Accommodation - #16 AWG - #8 AWG solid or stranded copper wire.
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

General

Catalog Number	IG2310
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Item Type	Single Flush Receptacles
Material	Nylon
Material - Mounting Hardware	Screw Mounting
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Specifications	• Base - RTP • Contacts - Brass • Face - Nylon • Mounting Strap - Brass • Terminal Screws - #10 - 32 Brass
UPC	783585872209

Dimensions

Dimensions	3.28 in x 1.24 in x 1.70 in
Display Size	Standard Sized Product

Height	1.7 in
Length	3.28 in
Weight	0.25 lb
Width	1.24 in

Electrical Ratings

Amperage Rating	20 A
Connectivity	Back and Side Wired
Current / Amperage Rating	20 A
Current Rating	20 A
Dielectric Strength	Withstands 2,000V minimum
Phase	Single Phase
Voltage Rating	125 VAC
Voltage Rating Description	125V

Conductor Related

Number Of Wires	3-Wire
Wire Size	#16 AWG to #8 AWG

Certifications And Compliance

Industry Standard(s)	• Certified to CSA C22.2 No.42 • Fed.Spec. W-C-596 • Listed to UL 498
Nema Rating	5-20R
Standards - RoHS Compliance Status	CM

Logistics

Carton Quantity	10
Pallet Quantity	2520

Product Assets

[Catalogs - WDK Catalog Full 2024](#)
[Literature - EdgeConnect™ Technology FAQ](#)
[Specifications - IG2310](#)
[Warranty - Industrial & Commercial Products](#)