



**Ultra desoldering tweezers
WXUTS 150 W, 24 V (handle
without tips) for Active-Tip
Heating Technology**

Item No: T0051321099

Ultra desoldering tweezers WXUTS
150 W, 24 V (handle without tips) for
Active-Tip Heating Technology

KEY FEATURES

- + High-Performance / High-Productivity:
Extremely short heat-up time: 10 sec., Quick response time
- + Fastest Tweezer Tip Change:
Active Tip Cartridge System allows for easy exchange of soldering tip even with a hot desoldering tweezer, all without needing an extra tool or further adjustment
- + Ergonomics:
Improved comfort and safe handling with new ergonomic soft grips
- + Visual process control through RGB signal function:
Easy Tool Identification. Color customization enabled. (Choose between 12 colors)
- + Unique Intelligent 2-in-1 Desoldering Tweezer, 150 W, 24 V:
Supports Smart Pico (soldering or reworking SMDs such as 0402, 0201, 01005) & Micro Tweezers Tips for usage under the microscope. (Save one Tweezers Tool)
- + Integrated parameter memory:
Standby temperature and automatic switch-off time easily be stored in soldering iron, Parameters only need to be stored once; the desoldering tweezers can use them with any WXsmart station
- + Maximum Protection:
According to Military Standard, Mil-Spec compliant and fully compliant to IPC industry standards (IPC - TM-650 2.5.33 Measurement of Electrical Overstress from Soldering Hand Tools)
- + Highest Precision:
Maximum precision during the soldering process with short tip-to-grip distance and optimized tip design, Precise positioning with unique parallel sliding block guide, No alignment necessary after tip change with pairwise design, Adjustability functions with Allen key: 1.5mm possible if needed ($\pm 80^\circ$ rotation angle adjustment + vertical length adjustment of $\pm 1.2\text{mm}$), Intelligent Desoldering Tweezers Tips (allows Automatic Tip-Offset)
- + Compatible with:
WXsmart Control unit, WSR 210 Safety Rest, RTWUS Desoldering Tip Range

TECHNICAL DATA

Approximate Heating Time (50–350 °C/120–660 °F)	10 sec
ESD Safe	Yes
Power Consumption	150 W
Temperature Range °C	100 - 450
Temperature Range °F	200 - 850
Tip Range	RTUMS
UPC	037103371225
Voltage	24 V / AC
Works With	WXsmart